



COMMUNITY BOARD FEEDBACK PACKAGE

Please review this application and provide the required feedback.

DINING OUT NYC

COMMUNITY BOARD RECOMMENDATION FORM

This form is to be used by community boards during the cafe review process. Any comments from the community board should be recorded on this form and submitted to NYC DOT. For information pertaining to specific cafe design requirements, visit the Dining Out NYC website for program legislation, rules, and Setup Guides.

Business Name:
Cafe Location:
Application Number:
CB Feedback Deadline (on date or next business day):
NYCDOT Internal Use Only
Roadway Cafe Setup Comments:
Comments related to the cafe's physical footprint and dimensions:
Comments related to pedestrian flow (i.e., visbility, safety , potential crowding):
Comments related to potential conflicts with existing curb use (i.e., planters, bike racks, bus stops):
Overall recommendation for the cafe setup:
Suggested modifications related to the above referenced application:
ouggested modifications related to the above referenced application.

RESTAURANT DETAILS - Elsewhere Espresso - 20240731010050

Food Service Establishment Permit(FSEP)

FSEP#: 41689872

Expiration Date: 08/31/2025
DOHMH Status: CURRENT

Business Legal Name: ELSEWHERE ESPRESSO LLC

Assumed Name: ELSEWHERE ESPRESSO

Business Address: 335 EAST 6 STREET, NEW YORK, NY 10003

Venue Type: Restaurant (no bar)

Last updated from DOHMH: 01/13/2025

Restaurant Information Phone: (917) 502-6109

Email Address: elsewhereespresso@gmail.com

DOS Information
DOS ID#: 4271659

Process Name: The LLC

DOS Address: 335 EAST 6TH SREET, NEW YORK, NY, New York 10003

NYS Liquor Authority Information

NYSLA Serial No: 1343989 License Type: On-Premises

Name of License: ELSEWHERE ESPRESSO

Title of Representative: Owner

Name of Certificate Holder: ELSEWHERE ESPRESSO

Business hours

Sun: 7:00 AM- 10:00 PM Mon: 7:00 AM- 10:00 PM Tues: 7:00 AM- 10:00 PM Wed: 7:00 AM- 10:00 PM

Thurs: 7:00 AM- 10:00 PM

Fri: 7:00 AM- 10:00 PM

Sat: 7:00 AM- 10:00 PM

SECTION 1: Site Plan This Site Plan form is required to be uploaded in the "Roadway Site Plan" field of your online application. Refer to the How to Apply page in the Dining Out NYC website for more information about the application process. Identify Permitted Parking Location: Roadway Cafe Identify the Parking Sign in front of or around the area where your roadway setup would be located Site Plan Form Roadway cafes can only be placed in: 1. Parking spaces, which include: metered and non-metered spaces, commercial parking, alternate side parking, angled parking, Elsewhere Espresso Applicant Name: P1- Parking Space Elsewhere Espresso 2. Loading areas, including loading only, truck loading, hotel loading, and no parking zones. Restaurant Name: 3. Floating Parking Lane- a parking lane that is separated from the curb by a protected bicycle lane that is adjacent to the curb. P2- Loading Area P3- Floating Parking Lane FSEP Number: Use the space below to draw or upload your Site Plan representing your cafe perimeters, furniture, and clearances. Drawing Requirements Food service establishment frontage Line representing the establishment's space facing the sidewalk · Length Label Street names: Labels on each street Road 0 = CUCIA Sidewalk shown as: Line representing street curb Roadway shown as: · Width of curbside lane Cafe perimeter shown as: Barrier Barrier Bacher · Lines indicating perimeter · Length and width Set-up furniture (tables, chairs, etc.) shown as: · Lines or symbols at approximate location within setup Elements (in Section 2 of this form) within 15 feet of cafe perimeter, shown AXO Lines or symbols · Distance from cafe perimeter Marhole Labels Utility coverings (water/gas valves, and 630

Restaurant frontage

Width of roadway cafe:

Length of roadway cafe:

pull boxes) shown as:

within the setup

North arrow

Symbols representing the location

Please provide distances from the Only provide a distance if the lister	d object is with	ects. hin 15 feet of your proposed setup. website for more information regarding	
Elements with minimum 15 feet clea			, clearances.
R01- Subway Stair: Open End	feet	R02- Fire Hydrant	feet
Elements with minimum 10 feet clea	arance from re		
R03- Subway Elevator Entrance	feet	R05-MTA Curb Cut	feet
R04- FDNY Curb Cut	feet		
Elements with minimum 5 feet clear	rance from ro	adway cafe:	
R06- Curb Cut	feet	R11- CitiBike/Bike Share Station	feet
R07- Emergency Exit Hatch	feet	R12- Bike Corral	feet
R08- Subway Stair: Closed End	feet	R13- Micromobility Station	feet
R09- Subway Elevator: Non-Entry	feet	R14- Drainage Infrastructure	feet
R10- Bus Stop Pole:			
Non- Approaching Side	feet		
Elements with minimum 3 feet clea	rance from ro	adway cafe:	
R15- Elevated Train Infrastructure	feet	R16-Transformer Vault	feet
Elements with minimum 1 foor and	6 inches clea	rance from roadway cafe:	
R17-Vent Infrastructure: utility vent poles, vent grates, subway grates	feet	R18- Manholes	inches
Elements with minimum 6 inches c	learance from	n roadway cafe:	
R19-Thermoplastic Marking	feet		
Roadway cafe distance from crosss	walks:		
R20- Adjacent to non-approaching side of crosswalk (min. 8 foot distance)	feet	crosswalk on from	ance required crosswalk on roaching side
R21- Adjacent to approaching (stopping) side of crosswalk (min. 20 foot distance)	feet	noir-approaching side	Jacking State
R22- No crosswalk present (maintain 20 feet from curb line of intersecting street)	feet		20.00

Check this box if none of the objects listed above are within 15 feet of the proposed setup.

SECTION 3: Material Requirements

- Please indicate which of the following materials will be part of your roadway cafe by checking the box next to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements.
- Refer to the Setup Guides in the Dining Out NYC website for more information regarding materials.

Materials Checklist:

Required

- Barriers (All of the following must be met)

 Maintained on all sides of the cafe except the side fronting the ground floor restaurant.
 - Not permanently affixed to the roadway.
 - 30-42 inches tall (excluding planting), and at least 4 inches in width.
 - Barriers are interconnected with each other.
 - Any cladding over the barriers is securely fastened or affixed.
 - Minimum 4 inches wide reflective strip on each barrier on the outward facing side.
 - Water-filled with a minimum of 150 pounds per linear foot of barrier length.

Optional - Only check the material categories you intend to use in your roadway cafe

Flooring (if using, all of the following must be met)

- Durable, lightweight, easily removable, mold-resistant, elevated from the ground level to allow for drainage, and removable to allow for cleaning.
- Flush with the curb line (except if located on a slope, be flush to the greatest extent feasible), and compliant with applicable accessibility requirements.
- Maintains a 6 inch covered channel between curb and base of flooring to allow for drainage.

Furnishings (if using, all of the following must be met)

Lightweight and easily movable.

Vertical Screenings (if using, all of the following must be met)

- Located between the barrier and 6 feet above the cafe base or floor.
- Located on the roadway facing side, does not extend the beyond the perimeter of the roadway cafe, and is not affixed to the outward facing side of barriers.
- Easily removable, comprised of non-opaque, fire-grade, and wind resistant materials.
- If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.

Overhead Coverings/ Umbrellas (if using, all of the following must be met)

- Minimum of 7 feet and maximum of 10 feet from the base or floor of the roadway cafe.
- Has a weighted base and any support structures are not affixed to the outward facing side of barriers, are of sufficient size and strength, made of durable materials, and free of defects.
- Easily removable, comprised of fire-grade and wind resistant materials.
- If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.

Lighting and Electrical Connections (if using, all of the following must be met)

- Any lighting is outdoor rated, properly secured, and lightweight.
- At least 14 feet above sidewalk, and 18 feet above roadway.
- Not attached to any City property, including street trees.
- Electrical work complies with the applicable requirements set forth in DOT's rules and the New York City Electrical Code. Please note that this may require additional permits from DOB or FDNY, and/or approval from the Landmarks Preservation Commission (LPC) as applicable.