



## COMMUNITY BOARD FEEDBACK PACKAGE

Please review this application and provide the required feedback.

#### **DINING OUT NYC**

#### **COMMUNITY BOARD RECOMMENDATION FORM**

This form is to be used by community boards during the cafe review process. Any comments from the community board should be recorded on this form and submitted to NYC DOT. For information pertaining to specific cafe design requirements, visit the Dining Out NYC website for program legislation, rules, and Setup Guides.

Business Name:
Cafe Location:
Application Number:
CB Feedback Deadline (on date or next business day):
NYCDOT Internal Use Only
Roadway Cafe Setup Comments:
Comments related to the cafe's physical footprint and dimensions:
Comments related to <b>pedestrian flow</b> (i.e., visbility, safety , potential crowding):
Comments related to potential conflicts with <b>existing curb use</b> (i.e., planters, bike racks, bus stops):
Overall recommendation for the cafe setup:
Suggested modifications related to the above referenced application:
ouggested modifications related to the above referenced application.

#### RESTAURANT DETAILS - Nowon - 20240731010031

Food Service Establishment Permit(FSEP)

FSEP#: 50099434

Expiration Date: 10/31/2025
DOHMH Status: CURRENT

Business Legal Name: NOWON INC

Assumed Name: NOWON

Business Address: 507 E 6TH ST, NEW YORK, NY 10009

Venue Type: Restaurant (with bar)

Last updated from DOHMH: 01/13/2025

Restaurant Information Phone: (646) 692-3867

Email Address: JAE@NOWONUSA.COM

DOS Information
DOS ID#: 5604131

Process Name: NOWON INC

DOS Address: 507 E. 6TH STREET, NEW YORK, New York 10009

NYS Liquor Authority Information

NYSLA Serial No: 1340827 License Type: On-Premises Name of License: JAE S LEE

Title of Representative: PRESIDENT

Name of Certificate Holder: NOWON INC

**Business** hours

Sun: 5:00 PM- 11:00 PM Mon: 5:00 PM- 11:00 PM Tues: 5:00 PM- 11:00 PM Wed: 5:00 PM- 11:00 PM

Thurs: 5:00 PM- 11:00 PM Fri: 5:00 PM- 12:00 AM

Sat: 5:00 PM- 12:00 AM

#### **SECTION 1: Site Plan**

- This Site Plan form is required to be uploaded in the "Roadway Site Plan" field of your online application.
- Refer to the How to Apply page in the Dining Out NYC website for more information about the application process.

#### **Identify Permitted Parking Location:**

- Identify the Parking Sign in front of or around the area where your roadway setup would be located.
- Roadway cafes can only be placed in:
  - Parking spaces, which include: metered and non-metered spaces, commercial parking, alternate side parking, angled parking and seasonally restricted parking.
  - 2. Loading areas, including loading only, truck loading, hotel loading, and no parking zones.
  - 3. Floating Parking Lane- a parking lane that is separated from the curb by a protected bicycle lane that is adjacent to the cur

rking,	P1- Parking Space
	P2- Loading Area
urb.	P3- Floating Parking Lane

DINING	NEW YORK CITY	Eric Adams Mayor
行うの		Ydanis Rodrigue Commissioner

### Roadway Cafe Site Plan Form

Applicant Name:	
Restaurant Name:	
ESED Number	

#### **Drawing Requirements**

## Food service establishment frontage shown as:

- Line representing the establishment's space facing the sidewalk
- Length
- Label

#### Street names:

Labels on each street

#### Sidewalk shown as:

Line representing street curb

#### Roadway shown as:

Width of curbside lane

#### Cafe perimeter shown as:

- Lines indicating perimeter
- Length and width

## Set-up furniture (tables, chairs, etc.) hown as:

Lines or symbols at approximate location within setup

## Elements (in Section 2 of this form) within 15 feet of cafe perimeter, shown as:

- Lines or symbols
- Distance from cafe perimeter
- Labels

## Utility coverings (water/gas valves, and pull boxes) shown as:

Symbols representing the location within the setup

North arrow

grane a parking lane that to depart tea from the darb by a proteoted bioyofe lane that to adjudent to the darb.	P3- Floating Parking Lane	FSE
Use the space below to draw or upload your Site Plan representing your cafe perimeters, furniture, and cl	earances.	
		F s
		s ·
		:
		s
		•
		s
		Ш.
		R
		C
		.
		Ш.
		S
		E W
		a
		:
		U
		•
		N
Length of roadway cafe:feet Width of roadway cafe:feet		

#### SECTION 2: Required Clearances

(min. 20 foot distance)

(maintain 20 feet from curb line of intersecting

R22- No crosswalk present

street)

- · Please provide distances from the following objects.
- Only provide a distance if the listed object is within 15 feet of your proposed setup.
- Refer to the <u>Setup Guides</u> in the Dining Out NYC website for more information regarding clearances.

Elements with minimum 15 feet clearance from roadway cafe:			
R01- Subway Stair: Open End	feet	R02- Fire Hydrant	feet
Elements with minimum 10 feet of	learance from re	oadway cafe:	
R03- Subway Elevator Entrance	feet	R05- MTA Curb Cut	feet
Elements with minimum 5 feet cl	earance from roa	adway cafe:	
R06- Curb Cut  R07- Emergency Exit Hatch  R08- Subway Stair: Closed End  R09- Subway Elevator: Non-Entry  R10- Bus Stop Pole:  Non- Approaching Side	feetfeetfeetfeet	R11- CitiBike/Bike Share Station R12- Bike Corral R13- Micromobility Station R14- Drainage Infrastructure	feetfeetfeetfeet
Elements with minimum 3 feet cl	earance from roa	adway cafe:	
R15- Elevated Train Infrastructure	feet	R16- Transformer Vault	feet
Elements with minimum 1 foor ar	nd 6 inches clear	rance from roadway cafe:	
R17- Vent Infrastructure: utility vent poles, vent grates, subway grates	feet	R18- Manholes	inches
Elements with minimum 6 inches	clearance from	roadway cafe:	
R19- Thermoplastic Marking	feet		
Roadway cafe distance from cros	sswalks:		
R20- Adjacent to non-approaching side of crosswalk (min. 8 foot distance)  R21- Adjacent to approaching (stopping) side of crosswalk	feet	crosswalk on fr	istance required om crosswalk on pproaching side

# feet feet

Check this box if none of the objects listed above are within 15 feet of the proposed setup.

#### SECTION 3: Material Requirements

- Please indicate which of the following materials will be part of your roadway cafe by checking the box next to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements.
- Refer to the <u>Setup Guides</u> in the Dining Out NYC website for more information regarding materials.

#### **Materials Checklist:**

*Required*
Barriers (All of the following must be met)
Maintained on all sides of the cafe except the side fronting the ground floor restaurant.
Not permanently affixed to the roadway.
30-42 inches tall (excluding planting), and at least 4 inches in width.
Barriers are interconnected with each other.
Any cladding over the barriers is securely fastened or affixed.
Minimum 4 inches wide reflective strip on each barrier on the outward facing side.
Water-filled with a minimum of 150 pounds per linear foot of barrier length.
*Optional - Only check the material categories you intend to use in your roadway cafe*
Flooring (if using, all of the following must be met)
Durable, lightweight, easily removable, mold-resistant, elevated from the ground level to allow for drainage, and removable to allow for cleaning.
Flush with the curb line (except if located on a slope, be flush to the greatest extent feasible), and compliant with applicable accessibility requirements.
Maintains a 6 inch covered channel between curb and base of flooring to allow for drainage.
Furnishings (if using, all of the following must be met)
Lightweight and easily movable.
Vertical Screenings (if using, all of the following must be met)
Located between the barrier and 6 feet above the cafe base or floor.
Located on the roadway facing side, does not extend the beyond the perimeter of the roadway cafe, and is not affixed to the outward facing side of barriers.
Easily removable, comprised of non-opaque, fire-grade, and wind resistant materials.
If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.
Overhead Coverings/ Umbrellas (if using, all of the following must be met)
Minimum of 7 feet and maximum of 10 feet from the base or floor of the roadway cafe.
Has a weighted base and any support structures are not affixed to the outward facing side of barriers, are of sufficient size and strength, made of durable materials, and free of defects.
Easily removable, comprised of fire-grade and wind resistant materials.
If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.
Lighting and Electrical Connections (if using, all of the following must be met)
Any lighting is outdoor rated, properly secured, and lightweight.
At least 14 feet above sidewalk, and 18 feet above roadway.
Not attached to any City property, including street trees.
Electrical work complies with the applicable requirements set forth in DOT's rules and the New York City Electrical Code. Please note that this may require additional permits from DOB or FDNY, and/or approval from the Landmarks Preservation Commission (LPC) as applicable.